

Fox ESS

ECS SERIES

ECS4300H-H2/H3/H4/H5/H6/H7

Model	ECS4300H -H2	ECS4300H -H3	ECS4300H -H4	ECS4300H -H5	ECS4300H -H6	ECS4300H -H7
ELECTRICAL CHARACTERISTICS						
Battery Type	LiFePO4 Prismatic Cell					
Battery Module	1*CM4300H 1*CS4300H	1*CM4300H 2*CS4300H	1*CM4300H 3*CS4300H	1*CM4300H 4*CS4300H	1*CM4300H 5*CS4300H	1*CM4300H 6*CS4300H
Nominal Capacity[Wh]	8290	12440	16590	20740	24880	29030
Nominal Voltage [V]	115.2	172.8	230.4	288	345.6	403.2
Operating Voltage[V]	97.2 ~ 131.4	145.8 ~ 197.1	194.4 ~ 262.8	243 ~ 328.5	291.6 ~ 394.2	340.2 ~ 459.9
Recommend Discharge Current [A]	35					
Max.Charge/Discharge Current [A]	50					
Peak Discharge Current [A]	65 @30sec					
Battery Pack Round-Trip Efficiency [%]	>95					
Depth of discharge [%]	90					
Cycle Life* ¹	≥6000					
Communication	CAN					
Display	CS: LED*1, CM: LED*6					
Scalability	Max. 7 Modules in Series					
OPERATING CONDITIONS						
Installation Location	Outdoor/ Indoor (Stand)					
Operating Temperature [°C]* ²	Charge: 0 ~ 55 Discharge: -10 ~ 55					
Storage Temperature [°C]	-20 ~ 55					
Cooling method	Natural Convection					
Humidity [%]	5 ~ 95 (No Condensing)					
Altitude [m]	Max. 2,000					
Mechanical Characteristics						
Dimensions (W*H*D) [mm]	570*350*380	570*470*380	570*590*380	570*710*380	570*830*380	570*950*380
Weight [kg]	75.6±1	112.5±1.5	148.3±2	184.7±2.5	221±3	257.4±3.5
Certificates						
Safety	IEC 62619					
EMC	IEC 61000-6-1/2/3/4					
Transportation	UN38.3					
Ingress Protection	IP65					

*1, 25°C, @90% DOD, 0.5C charging/discharging.

*2, Charge derating will occur between 0°C and +15°C.